

Wall mount suction samplers

acc. ISO 5667 / EN 16479 / NEN 6600-1

SAMPTEC.NL

Next generation samplers, sustainable by design!

Peristaltic



Enclosure material	ABS
Colour	RAL 5021 Water blue
Power supply	110/230 VAC 50/60Hz - 6 Amp
Sampling type	Suction peristaltic
Pump	Peristaltic 24 VDC Bi-Directional
Internal hardware	ULV
H max	6 mtr
Tube diameter	9 mm
Water detection via	Conductivity relay or timer
Sample volume	Via software setting
Safety alarm	Pump cover open = no sample
Acc.	EN 16479 / ISO 5667-10
Size & weight	200 x 300 x 350 mm ± 7 Kg

Vacuum



Enclosure material	ABS
Colour	RAL 5021 Water blue
Power supply	110/230 VAC 50/60Hz - 6 Amp
Sampling type	Suction by vacuum
Pump	1 or 2 brushless 24 VDC deep vacuum
Internal hardware	ULV
H max	7 mtr
ID tube diameter	9 / 12 / 16 / 19 mm standard 13 mm
Water detection via	Conductivity relay + extra alarm relay
Sample volume	from 20 to 250 ml
Acc.	EN 16479 / ISO 5667-2 & 10 / NEN 6600-1
Size & weight	200 x 300 x 420 mm ± 7 Kg
Sample chamber	via bracket quick connect

Controller options

Samptec PLC

Sample on:	Flow pulse / Flow current / Time / Batch
Next container on:	Time / Overflow protection
Scheduler:	Start on date
Temperature control:	Cool unit & heater



Upgrade to **SIEMENS** S7 - 1200 + MTP400

- + Standard functions
 - + Logging of flow & samples direct on usb
 - + Sample on calendar
 - + Open channel flowmeter
-
- + Remote control via Lan or SIM card
 - + Pump controller



Product patented



MADE IN HOLLAND



Samptec® is a TEC42 product
TEC42.COM B.V.
Mijlweg 9-4, 4131PJ Vianen, The Netherlands

info@TEC42.com
+31 85 0600642